

**TORO**

**TITAN<sup>®</sup> HD with MyRIDE<sup>®</sup>**  
1500 SERIES ZERO TURN MOWERS

**NEW!**



**BUCKET MOUNT**



**TRIMMER MOUNT**



**UNIVERSAL TOOL MOUNT**



**INNOVATIVE TOOL CARRYING**

TITAN HD provides you the unique ability to easily attach your tools and accessories directly to the mower with the innovative tool-mounting brackets, saving you time and improving your efficiency.

\*Tool-mounting kits are optional attachments.



## SPECIFICATIONS


MODEL	74465TE - MYRIDE® <b>NEW!</b>	74466TE - MYRIDE® <b>NEW!</b>
CUTTING WIDTH	122 cm	▶ 132 cm
DEFLECTOR WIDTH	160 cm	▶ 172 cm
ENGINE	TORO® 708cc, 24.5 hp (18.3 kW)	TORO® 708cc, 24.5 hp (18.3 kW)
GROUND SPEED	0-13 km/h (0-8 mph)	0-13 km/h (0-8 mph)
DECK TYPE	TURBO FORCE® Side Discharge	TURBO FORCE Side Discharge
DECK DEPTH	127 mm	127 mm
HEIGHT OF CUT	38-127 mm	38-127 mm
ROPS	Folding	Folding
DECK SPINDLES	20.3 cm Aluminium, Sealed Bearings, 2.5 cm shaft	20.3 cm Aluminium, Sealed Bearings, 2.5 cm shaft
DRIVE TYRES	56 cm x 24 cm x 30 cm	56 cm x 24 cm x 30 cm
CASTER TYRES	33 cm x 16.5 cm - 15.2 cm Flat-free Semi-Pneumatic	33 cm x 16.5 cm - 15.2 cm Flat-free Semi-Pneumatic
FUEL/CAPACITY	Petrol/26.5 litres	Petrol/26.5 litres
WEIGHT	421 kg	429 kg

▶ = Enhanced or step-up feature



### TORO® COMMERCIAL-GRADE ENGINES

Powerful Toro commercial-grade engines provide professional quality performance. Heavy-duty Donaldson® canister style air filtration system protects the engine from contaminants and prolongs product life.



### COMMERCIAL-GRADE HYDRAULICS

The integrated pump and wheel motor uses proven commercial hydraulic components while eliminating hoses and other potential leak points. You'll get a smoother, faster response while enjoying an even more reliable machine.



### TURBO FORCE® CUTTING DECKS

Landscape professionals worldwide rely on Toro's patented TURBO FORCE® decks for outstanding quality of cut and durability. Nothing cuts as well as TURBO FORCE.



### MYRIDE® MAXIMUM COMFORT

The MyRIDE Suspension System features a suspended operator platform and adjustable rear shocks to provide a superior ride.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.

### toro.com

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 U.S.A.  
Phone: (1) 952 888 8801  
Fax: (1) 952 887 8258

©2018 The Toro Company.  
All Rights Reserved.  
GB 200-8002NA



facebook.com/ToroCompany  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope

**TORO®**

**Count on it.**